## MATERIAL SAFETY DATA SHEET

## SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: GOLD MEDALLIST

CHEMICAL FAMILY: Hydrocarbon Blend

**OIL MODIFIED URETHANE** 

PRODUCT TYPE: Floor Sealer

**PRODUCT #:** 1144

SUPPLIER'S NAME: Superior Sanitary Supply

## SUPPLIER'S ADDRESS:

176 Front Street Hempstead, NY 11550

EMERGENCY PHONE: 800-535-5053

DATE ISSUED: 11/2004

DOT CLASSIFICATION: NONE

DOT SHIPPING NAME: NONE

## HAZARD RATING:

HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0 PERSONAL PROTECTION: B

SECTION 2 - INGREDIENTS INFORMATION				
CHEMICAL NAME	CAS NO.	% / WT.	THRESHOLD LIMIT VALUE	
SOLVENT NAPTHA	64742-38-7	TO 50	100ppm	
POLYURETHANE (BLEND)	68038-49-3	TO 30	N/E	
POLYMER (BLEND)	66070-60-8	TO 30	N/E	

\*An asterisk indicates the toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372:

SECTION 3 - PHYSICAL DATA		SECTION 4 - REACTIVITY DATA	
BOILING RANGE (F): 323-390 °F	SPECIFIC GRAVITY: 0.89	STABILITY: Stable	
VAPOR PRESSURE: 2mmHg	VAPOR DENSITY: 4.9	HAZARDOUS POLYMERIZATION: Will Not Occur	
% VOLATILE: 40-45	pH: N/A	INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents	
SOLUBILITY IN WATER: Insoluble	EVAPORATION RATE: .12	HAZARDOUS DECOMPOSITION PRODUCTS: Normal products of combustion	
PHYSICAL DESCRIPTION: Clear Liquid, Solvent Odor			
SECTION 5 - FIRE & EXPLOSION HAZARD DATA		SECTION 6 - STORAGE & HANDLING INFORMATION	
FLASH POINT: 150 °F FLAMMABILITY: Combustible EXTINGUISHING MEDIA: Foam, Dry Chemical, CO <sub>2</sub> SPECIAL FIRE FIGHTING PROCEDURES: Floor may be slippery UNUSUAL AND EXPLOSION HAZARDS: Closed drums may explode		SPECIAL PRECAUTIONS: Keep out of reach of children. Use only in well ventilated area. For institutional and industrial use only. For use by trained personnel only. Store and keep in closed container, in a cool place. Avoid freezing. <b>DANGER</b> - After container has been emptied, it may contain explosive and harmful vapors and residue. Keep away from heat, sparks and flames. Welding or cutting container may cause container to explode, resulting in injury or death.	
SECTION 7 - HEALTH HAZARD DATA		<b>SECTION 8 - FIRST AID PROCEDURE</b>	
EYES: May cause irritation.	EXPOSURE LIMITS: N/E	EYES: Flush with running water for 15 minutes.	
SKIN: May cause irritation. CARCINOGENICITY:   NTP: Not listed		SKIN: Wash off with soap and water.	
INHALATION: May cause irritation to u	pper tract. IARC: Not listed	<b>INHALATION:</b> Remove to fresh air.	
<b>INGESTION:</b> May cause irritation of mucous	membranes. OSHA: Not regulated	INGESTION: Do not induce vomiting.	
MEDICAL CONDITION AGGRAVATED BY EXPOSURE: Person with present skin disorder may be more susceptible to irritation.		Drink plenty of water. If unconscious or in convulsion, take to hospital or physician	
SECTION 9 - PRECAUTIONS FOR SAFE HANDLING		SECTION 10 - SPILL OR LEAK	
<b>RESPIRATORY PROTECTION:</b> No special requirements.		SPILLAGE: Dike & contain spill, absorb the liquid.	
PROTECTIVE GLOVES: Chemical resistant.		DISPOSAL: Scoop or shovel solid material into a suitable container for	
VENTILATION: Good ventilation required.		recovery or disposal. Area may become slippery. Flush cleaned area with water.	
EYE CONTACT: Goggles or Face Shie	ld.	Dispose according to local, state and federal requirements.	

N/D = Not Determined, N/E = Not Established, N/A = Not Applicable THIS PRODUCT SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATION SAFETY AND HEALTH.