MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION Identity (As Used on Label and List): Multi-Clean Premier Product Class: Water-borne floor polish Emergency Telephone Number: 800-2 800-255-3924 Telephone Number for Information: 651-481-1900 Manufacturer's Name and Address: Multi-Clean®, A Division of Minuteman International, Inc. 600 Cardigan Road Shoreview, MN 55126 SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS Hazardous Components (Specific Chemical Identity): Chemical Common Name(s) Emulsified acrylic polymers 10 - 30 (proprietary) Diethylene glycol monoethyl ether В 3 - 7 CAS #111-90-0 C Tributoxyethyl phosphate 1 - 5 CAS #78-51-3 D Emulsified polymer wax 1 - 5 (proprietary) F Water 60 - 100CAS #7732-18-5 Dipropylene glycol methyl ether CAS #34590-94-8 F 2 - 6 SECTION III - HAZARDS IDENTIFICATION **Emergency Overview** Appearance and Odor: Milky white liquid, mild acrylic odor Primary Hazards: Irritant **Potential Health Hazards** Route(s) of Entry: Skin Absorption: X Ingestion: Inhalation: X Eye: May cause irritation on contact. May cause irritation on prolonged or repeated contact. Ingestion: May be harmful if swallowed. Inhalation: No effects expected. Signs and Symptoms of Exposure: Irritation on direct contact. Carcinogenicity: NTP? No IARC Monographs? OSHA Regulated? No Target Organ (s): No additional data Medical Conditions Generally Aggravated by Exposure: N. Av. Health Hazards, Chronic: N. Av. **SECTION IV - FIRST AID MEASURES Emergency and First Aid Procedures:** If Swallowed: Do not induce vomiting. Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. Eye Contact: Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. Skin Contact: Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse. Sources Used: Raw material data, general toxicology from the trade for similar **SECTION V - FIRE FIGHTING MEASURES** Flammability: No Flash Point (method used): Autoignition Temperature: None Flammable Limits: N. Ap. LEL UEL Extinguishing Media N. Ap. Water? Water Fog? Foam? Alcohol Foam? **Dry Chemical?** CO2? Vaporizing Liquid? Other? Special Fire Fighting Procedures: N. Ap. Unusual Fire and Explosion Hazards: N. Av.

TDG Flammability Classification: Non-flammable

Sensitivity to Mechanical Impact: None Sensitivity to Static Discharge: None

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled:

Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water

SECTION VII - HANDLING AND STORAGE

Precautions to be Taken in Handling and Storing:

Storage Temperature: Minimum 40°F (4°C); Maximum 100°F (38°C) Other Precautions: Keep out of reach of children. Keep from freezing.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not required
Ventilation: Local Exhaust: Not required

Special: Not required

Mechanical (General): Normal good ventilation sufficient.

Other: Not required

Protective Gloves: Natural rubber or synthetic.

Eye Protection: Approved safety goggles or glasses. Footwear: Not required

Other Protective Clothing or Equipment: Not required

Work/Hygienic Practices: Do not contaminate food or beverages with cleaning chemicals

	DUDYOLO AL VOLUENIO AL O		
SECTION IX -	PHYSICAL/CHEMICAL C	CHARACTERISTICS	

Boiling Point: Approximately 212°F **pH**: 8-9 Specific Gravity (H20) = 1: 1.034 % Volatile: 80 Vapor Density (Air = 1): > 1 Odor Threshold: N. Av. Evaporation Rate (Butyl Acetate = 1): N. Av. Oil/Water Distribution Solubility in Water: Complete Coefficient: N. Av.

Vapor Pressure (MM HG): N. Av.

Melting Point: N. Ap.

SECTION X - STABILITY AND REACTIVITY

Unstable: Stability: Stable:

Conditions to Avoid: N. Ap.

Incompatibility (materials to avoid): N. Av. Hazardous Decomposition or By-products: N. Av.

Hazardous Polymerization: May occur: Will not occur: X

Conditions to Avoid: N. Ap.

SECTION XI - TOXICOLOGICAL INFORMATION

Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
Α	N. Ap.	N. Ap.	N. Ap.	N. Av.	N. Av.
В	N. Ap.	N. Ap.	N. Av.	5,000 mg/kg	> 200 mg/IL
С	N. Ap.	N. Ap.	N. Av.	N. Av.	N. Av.
D	N. Ap.	N. Ap.	N. Av.	N. Av.	N.v.
E	N. Ap.	N. Ap.	N. Ap.	N. Ap.	N. Ap.
F	100 ppm	100 ppm	100 ppm	> 5 ml/kg	N. Av.
	(skin)	(skin)	(skin)	(rat, oral)	

Teratogen, Mutagen, Reproductive Toxin Status: No Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av. Chemical Fate Information: N. Av.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Solution may contain zinc. Coagulate with ferric chloride or sulfate and then lime. Decant the clear liquid to a sewer. Dispose of the coagulum by sanitary landfill or incinerator. Follow all existing pollution control ordinances.

RCRA Hazard Class: None

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: Buffing or polishing compound

UN Number: N. Ap. Packing Group: N. Ap.

SECTION XV - PREPARATION DATA

Prepared By: Mike Tarvin Telephone Number: 651-481-1900

Date: 4/08

SECTION XVI - REGULATORY INFORMATION

US Federal Regulations

TSCA Status: All ingredients listed. CERCLA Reportable Quality: None

SARA Title III

Section 302 Extremely Hazardous Chemicals: None Section 311/312 Hazard Category: Immediate health hazard Section 313 Toxic Chemicals: Diethylene glycol monoethyl ether

(glycol ether) State Regulations

International Regulations

WHMIS Controlled Product Hazard Class: D2B

SECTION XVII - OTHER INFORMATION

N. Ap. - Not Applicable; N.Av. - Not Available

NFPA SYSTEM

1 A. Health Hazard 0 A. Reactivity Hazard 0 A. Fire Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL